

SlimLine 38



- ✓ profile with a construction depth from 3" up to 3-7/8" (76-99 mm) – depends of version
- ✓ overall glazing thickness up to 2-1/8" (55 mm)
- ✓ Sobinco tilt-and-turn hardware
- ✓ 3 aesthetic options: Classic, Ferro, Cubic
- ✓ powder coating in any color from the RAL palette
- ✓ we lacquer in the full RAL K7 color palette and, on request, in other colors (use powder code)

0,35

U-Factor | simulated with double glazing*

3

Gaskets

3

Chambers

The system's versatility is ensured by the availability of three aesthetic variants of profiles: Classic, Ferro and Cubic. The possibility of almost any mixture of frames, sashes and girders between variants makes it easy to adapt the ideal configuration.

SlimLine 38 Classic system has been developed for modern architecture focused on sprawling glazing. This variant mimics the slender look of steel windows with sloping exterior part.

SlimLine 38 Cubic is a system of aluminium windows inspired by the style of steel windows. The geometric, minimalist form of the SlimLine 38 Cubic profiles allows them to be used in modern construction and in the renovation of older buildings.

SlimLine 38 Ferro aluminum window system presents a minimalist elegance reminiscent of traditional steel windows. It was created for use in renovation projects and to complement modern designs that celebrate classic materials such as brick and steel.

SlimLine 38 can be equipped with a thermal break, which, together with three gaskets and a triple glazing package,

provides the windows with very good thermal parameters.

* The above U-factor is a general achievable value for this window system. The detailed value can be provided with the selected IGU and product type.